

LED D5




Type	Watt	Lumen**	A	B	kg	Code
LED Downlighter D5S	14W	1936lm	80	230	0,8	D500
LED Downlighter D5S	20W	2695lm	80	230	0,8	D500
LED Downlighter D5S	28W	3894lm	80	230	0,8	D500
LED Downlighter D5	14W	1936lm	120	180	1,2	D501
LED Downlighter D5	20W	2695lm	120	180	1,2	D501
LED Downlighter D5	28W	3894lm	120	180	1,2	D501

* Of vergelijkbare kwaliteit.

** Volgens opgave 09-2020. Gemeten bij 4000K, tolerantie van 10% van toepassing conform richtlijnen IEC.

Maatvoering A, B in mm



Optioneel



Montage



Stralingshoek



Lichtkleur



Specificaties	
Behuizing	Staal
Beschermingsklasse (IP)	IP20
Energielabel	A++
BREEAM / EIA	Nee
Garantie	5 jaar fabrieksgarantie***
Levensduur (uur)	60.000 (L80C10)****
Kleurweergave (CRI/RA)	>85
Kleurafwijking (SDCM)	Mac Adam <3
Flicker	<2%
Spanning (V)	220-240
Powerfactor (P)	>0,95
Driver	TCI of vergelijkbaar

Omgevingstemperatuur
-20 tot 30°C



*** Max Tc temp. 65°C gemeten bij Ta 25°C

**** Conform Lighting Europe, "Evaluating the performance of LED based Luminaires"